



OLYMPIA CLADDING

OLYMPIA CLADDING

Olympia Cladding is named for Windfall's hometown and made from the Pacific Northwest's regional Red Alder. With a silky-smooth face, the cladding is available in 10 translucent colors which allow the natural features to shine through.

MATERIAL AND SURFACE

Red Alder (FSC mixed credit)
Janka hardness scale 590
Tongue and groove profile
Open knots allowed up to 3/8" and not filled

DIMENSIONS

 $\frac{1}{2}$ " thick x 3" wide Loose sticks are 2' - 8' random lengths

Six standard panel sizes:

- 18" x 18" (full length sticks)
- 18" x 36" (full length sticks)
- 36" x 36" (full length sticks)



• 18" x 54" (random length sticks)

• 18" x 90" (random length sticks)

• 24" x 96" (random length sticks)

FINISHES / ADHESIVES

Low VOC waterborne clear coat, 66 g/L Stain VOC: 7 g/L Bone and Dove Stain VOC: 0 g/L Citrine, Monarch, Earthen, Sage, Slate, Auburn, Espresso and Raven

Sheen: Dead Flat 120

Adhesive VOC: 0 g/L (NAUF compliant)

FIRE RATING

Class C as-is in native form, Class A and B Available upon request

SEISMIC RATING

Available upon request

POTENTIAL LEED CREDITS

Materials & Resources Credit 5: Regional Materials (500 mi of Tumwater, WA)

Materials & Resources Credit 7: Certified Wood

Indoor Environmental Quality Credit 4.2: Low-emitting Materials - Paints & Coatings

FSC CHAIN OF CUSTODY SA-COC-002372-3 when available








OLYMPIA CLADDING

STAIN OPTIONS





SAMPLES

Please Contact Us for your request or make your request at windfall.design

LEAD TIME

3-5 weeks depending on area, and ship date provided upon order

MOQ

No Minimum Order Quantity

DISCLAIMER: Since wood is a natural material, there are variations, including knots, texture and grain from piece to piece. The wood used may vary from the wood used in samples or product photography due to the inherent characteristics of the material. In turn, no representation, warranty and/or guarantee is made with respect to the precise color, luster or appearance of finishes.







Olympia Cladding INSTALLATION METHODS

STICKS





Tongue + groove cladding (loose sticks)Traditional install with nails + adhesive

Panels installed using fixed mounted fastener

Cambio by Windfall panels Installed with patented magnetic wall system.

DESIGN YOUR WALL



USE OUR VISUALIZER TOOL TO DESIGN YOUR WALL. RECEIVE AN INVENTORY LIST, SEND TO OUR TEAM FOR A QUOTE.

