



OLYMPIA CLADDING

OLYMPIA CLADDING

Olympia Cladding is named for Windfall's hometown and made from the Pacific Northwest's regional Red Alder. With a silky-smooth face, the cladding is available in 10 translucent colors which allow the natural features to shine through.

MATERIAL AND SURFACE

Red Alder (FSC mixed credit)
Janka hardness scale 590
Tongue and groove profile
Open knots allowed up to 3/8" and not filled

DIMENSIONS

1/2" thick x 3" wide
Loose sticks are 2' - 8' random lengths

Six standard panel sizes:

- 18" x 18" (full length sticks)
- 18" x 36" (full length sticks)
- 36" x 36" (full length sticks)
- 18" x 54" (random length sticks)
- 18" x 90" (random length sticks)
- 24" x 96" (random length sticks)

FINISHES / ADHESIVES

Low VOC waterborne clear coat, 66 g/L
Stain VOC: 7 g/L Bone and Dove
Stain VOC: 0 g/L Citrine, Monarch, Earthen, Sage, Slate, Auburn, Espresso and Raven
Sheen: Dead Flat 120
Adhesive VOC: 0 g/L (NAUF compliant)

FIRE RATING

Class C as-is in native form, Class A and B
Available upon request

SEISMIC RATING

Available upon request



Olympia Cladding: Sage

POTENTIAL LEED CREDITS

Materials & Resources Credit 5: Regional Materials (500 mi of Tumwater, WA)

Materials & Resources Credit 7: Certified Wood

Indoor Environmental Quality
Credit 4.2: Low-emitting Materials
- Paints & Coatings


FSC CHAIN OF CUSTODY SA-COC-002372-3 when available





OLYMPIA CLADDING


STAIN OPTIONS




CLEAR




DOVE




BONE




CITRINE




MONARCH




EARTHEN




SLATE



AUBURN



ESPRESSO



RAVEN



SAMPLES

Please Contact Us for your request or make your request at windfall.design

LEAD TIME

3-5 weeks depending on area, and ship date provided upon order

MOQ

No Minimum Order Quantity


DISCLAIMER: Since wood is a natural material, there are variations, including knots, texture and grain from piece to piece. The wood used may vary from the wood used in samples or product photography due to the inherent characteristics of the material. In turn, no representation, warranty and/or guarantee is made with respect to the precise color, luster or appearance of finishes.






Olympia Cladding **INSTALLATION METHODS**

STICKS



Tongue + groove cladding
(loose sticks) Traditional install
with nails + adhesive

PANELS




Panels installed using
fixed mounted fastener

CAMBIO PANELS



Cambio by Windfall panels
Installed with patented
magnetic wall system.

DESIGN YOUR WALL



USE OUR VISUALIZER TOOL TO DESIGN
YOUR WALL. RECEIVE AN INVENTORY LIST,
SEND TO OUR TEAM FOR A QUOTE.